

NARROW STILE EXIT DEVICES

NARROW STILE

TH1100 - ED "crash bar" style exit devices are suitable for narrow, medium or wide stile aluminum and hollow metal doors. It is handed with a contoured cross bar that will fit doors up to 42" wide and can be field sized to accommodate narrow doors.


TH1100-ED

Specifications

- **MATERIAL** : Contoured anodized aluminum cross bar, stainless steel springs
- **LATCH CASE** : 1 1/4" wide x 7 1/4" long with 1/2" stainless throw
- **BACKSET** : 1 5/32" from edge of door to center line of device
- **STRIKE** : Rim mounted roller strike with shim
- **STILE** : 1 7/8" minimum
- **HANDING** : Handed, please specify RH or LH
- **DOOR THICKNESS** : 1 3/4" standard
- **DOOR WIDTH** : Up to 42", it can be field sized
- **MOUNTING HEIGHT** : Recommended installation at 39 13/32" from floor to center line of latch or strike assemblies
- **FASTENERS** : Furnished with sheet metal, machine screws and shoulder mounting studs with set screws
- **CYLINDER** : Accepts rim cylinder only
- **DOGGING** : Inside - push up dog pin rotate with screwdriver, Outside - by key cylinder
- **FINISHES** : Aluminum and duronotic



Grade - ANSI A156.3 Grade 2
Warranty - 10 years



- * For Left Hand Reverse Door; order RH device
- * For Right Hand Reverse Door; order LH device

EXIT DEVICE TRIMS



Rim cylinder
TH1100-RC



Pull Trim
w/ cyl. hole
TH1100-PLD



Dummy Pull Trim
TH1100-PLDUM



Exit Only Plate
TH1100-PLEO

- * For exit only application and outside control by rim cylinder
- * For new door application or existing hole less than 1 3/16"

CONCEALED VERTICAL ROD

TH1100 - CVR panic devices blend the utility of a vertical rod application with the appearance of a traditional panic device. It is non-handed and reversible with a contoured cross bar that will fit doors up to 42" wide and can be field sized to accommodate narrow doors.

TH1100-CVR

Specifications

- **MATERIAL** : Contoured anodized aluminum cross bar, stainless steel springs
- **LATCH CASE** : 1 1/4" wide x 7 1/4" long
- **DOOR HEIGHT** : 7' standard
- **BACKSET** : Center template on narrow door stile
- **STRIKE** : Top - flat mortise, Bottom - flat mortise or directly through threshold
- **PROJECTION** : 4 3/4"
- **STILE** : 1 7/8" minimum
- **HANDING** : Reversible, non-handed
- **DOOR THICKNESS** : 1 3/4" standard
- **DOOR WIDTH** : Up to 42"
- **MOUNTING HEIGHT** : 35 11/16" from floor to center line of the bottom latch case mounting stud
- **FASTENERS** : Furnished with sheet metal, machine screws and shoulder mounting studs with set screws
- **CYLINDER** : Accepts mortise type
- **DOGGING** : Inside - push up dog pin and rotate with screwdriver, Outside - by key cylinder
- **FINISHES** : Aluminum and duronotic



Grade - ANSI A156.3 Grade 2
Warranty - 10 years

EXIT DEVICE TRIMS



Mortise Cylinder
TH1100-BC



Cylinder Mounting Trim
TH1100-CVRPAD

- * For exterior key application must order TH1100-CVRPAD. Insert mortise cylinder in mounting trim and secure with locking ring nut, included.

ADDITIONAL ACCESSORIES



Manual Surface Bolt
TH1100-SB1-US26D