TOUCH BAR EXIT DEVICES

TOUCH BAR

TH1100EDTBAR "touch bar" style exit devices are suitable for all doors (aluminum, hollow metal, or wood) where there is no projection on the face. manufactured of extruded anodized aluminum, the TH1100EDTBAR is durable enough for the most demanding applications. a rim cylinder is not included, and the EDTBAR can also be used in conjunction with any of the exit device trims listed below.

TH1100EDTBAR

Specifications

- MATERIAL: Extruded anodized aluminum push bar, stainless steel springs
- LATCH: Stainless Steel, 3/4"throw 5/8"deadlatch
- BACKSET: 2 3/4"Covers 161 prep, includes latch & strike filler plates
- STRIKE: Surface mounted for 5/8"stop with shim
- PROJECTION: 2 1/2" 17/8"dogged
- STILE: 4 1/4"minimum
- HANDING: Reversible, non handed
- DOOR THICKNESS: 1 3/4"standard
- DOOR WIDTH: 36", can be field sized to 30" (48" available)
- MOUNTING HEIGHT: Recommended installation at 41" from finished floor to center line of push rail
- FASTENERS: Furnished with sheet metal and machine screws
- · CYLINDER: Accepts all key trims cylinder
- DOGGING: 1/2 turn hex key
- FIRE RATED: Available please specify
- FINISHES: Aluminum, duronotic, and stainless steel

SURFACE VERTICAL ROD


TH1100EDSV surface vertical rod panic device is the perfect choice for double doors without mullions. reversible for right or left hand doors, they are ideal for new construction or renovations. our EDSV panics can be used in conjunction with any of our exit device trims listed below.

TH1100EDSV

Specifications

- MATERIAL: Extruded anodized aluminum push bar, stainless steel springs
- LATCH: Top pullman type, Bottom bolt assembly
- DOORHEIGHT: 7' standard
- BACKSET: 2 3/4" on 41/2" minimum stile width if less than 41/2" backset becomes half of the exposed stile width
- STRIKE: Top surface mounted, Bottom flat mortise or into threshold, vertical/rim application use DBLST double dr.strike
- PROJECTION: 2 1/2"-17/8" dogged
- STILE: 4 1/2"minimum
- HANDING: Reversible, non-handed
- DOOR THICKNESS: 1 3/4"standard
- DOOR WIDTH: 36", can be field sized to 30"
- MOUNTING HEIGHT: Recommended installation at 41" from finished floor to center line of push rail.
- FASTENERS: Furnished with sheet metal and machine screws
- CYLINDER: Accepts rim, all trims Schlage "C" keyway
- DOGGING: 1/2turnhex key
- FIRE RATED : Available please specify
- FINISHES: Aluminum, Duronotic, and Stainless Steel





EXIT DEVICE TRIMS









Rim cylinder TH1100-RC

Pull Trim w/ cyl. hole

Dummy Pull Trim TH1100-PLDUM TH1100-PLED**





Entry Lever TH1100-LHED







Entry Ball TH1100-BALED



Dummv Handleset TH1100-DUMED



Night Latch Handleset TH110 0-NLED**



Entry Handleset TH1100-TPED*



W arranty -10years

EXIT DEVICE TRIMS







Rim cylinder TH1100-RC

Pull Trim w/ cvl. hole TH1100-PLED**

Dummy Pull Trim Exit Only Plate TH1100-PLDUM TH1100-PLEO



Entry Lever

Dummv

TH1100-LHED



Storeroom Lever

TH1100-LHST









Night Latch

TH1100-DUMED TH1100-NLED**





Entry Handleset TH1100-TPED*

Double Door Strike TH1100-DBLSTAL

^{*}TH1100-TPED entry trim accepts mortise cylinder,included **Toinstall cylinder on trim plate for 21/8" hole use mounting sleeve